

SUNMI T2s LITE Desktop POS

Flexible forms bring abundant experience

Performance breakthroughs on your fingertips.

High performance octa-core processor, up to 2.2Ghz. Equipped with large-capacity memory of 3GB RAM + 32GB ROM, T2s LITE allows you to experience unparalleled operation smoothness.

Anti-interference touch screen.

To realize your demand on worry-free touch experience in various environments, even near high-power devices, we employ an industrial-grade touch chip which is more resistant to EMI.

Unlock more possibilities with a VESA mount.

T2s LITE can be mounted with a VESA mount, enabling more applicable scenarios. For example, it can be used as a kitchen display of a KDS, greatly improving the restaurant operational efficiency.



Optional Accessories

NFC&MSR Card Reader

For NFC card reading and magnetic stripe card reading.



VESA mount

For more space-saving installation and more flexible use.



15.6"

Main: 15.6" FHD,
1920*1080



15.6" +10.1"

Main: 15.6" FHD,
1920*1080
Second: 10.1" HD,
1024*600



15.6" +15.6"

Main: 15.6" FHD,
1920*1080
Second: 15.6" FHD,
1920*1080



T2s LITE Tech Specs

Model Approved

Config 1: L1571 (Single-Display Version)
Config 2: L1572 (Dual-Display (small + big) Version)
Config 3: L1573 (Dual-Display (big + big) Version)

OS

Android 9.0
SUNMI OS

CPU

Kryo-260, Octa-core
up to 2.2GHz

Memory

32GB ROM + 3GB RAM
64GB ROM + 4GB RAM
(optional)

Camera

Face Recognition camera or
normal camera
(only for configuraion 2&3)

Display

Configuration 1: Main: 15.6" FHD, 1920*1080 Capacitive multitouch screen
Configuration 2: Main: 15.6" FHD, 1920*1080 Capacitive multitouch screen
Second: 10.1" HD, 1024*600 Capacitive multitouch screen
Configuration 3: Main: 15.6" FHD, 1920*1080 Capacitive multitouch screen
Second: 15.6" FHD, 1920*1080 Capacitive multitouch screen

Speaker

1* 1.2W

Bluetooth

BT2.1/3.0/4.0/5.0
BLE

Buttons

1* power button
2* volumn button

External Storage Card

Support Micro SD (TF)
Up to 64GB

SIM Card Slot

1* Micro SIM (optional)

LAN

LAN 100M

Network

2G&3G&4G (optional)

Wi-Fi

2.4G/5.0GHz
IEEE 802.11 a/b/g/n /ac

Interface

5* USB TypeA
1* RJ11 Serial port
1* RJ12 Cash drawer port
1* RJ45 LAN port
1* Audio jack
1* Power port
1* Micro-USB (debug)

Power Adapter

Input: AC100 ~ 240V/1.5A
Output: DC24V/1.5A

Dimensions

430*382*215mm
(max)

Weight

Configuration 1: 4.5 Kg
Configuration 2: 5.1 Kg
Configuration 3: 6.8 Kg

Environment

Operating temperature: 0°C ~ 40°C
Storage temperature: -20°C ~ 60°C

1.The usable memory may be less than the installed memory.

2.All specifications are subject to change without (prior) notice.