

Power Supply Device

# POS POWER BANK




reddot design award  
winner 2019


- Portable and rugged aluminum alloy housing.
- Provides suitable and efficient power supply.
- On-line UPS function.
- Low battery sound&light alarm.



Overcharge  
Protection



Over-discharge  
Protection



Short-circuit  
Protection



Error-proof  
Protection



# POS POWER BANK

## Technical specifications



### Battery

Li-Ion battery



### Rated capacity (2 Specs Available)

2500mAh/DC18V (45Wh)  
5000mAh/DC18V (90Wh)



### Rated output capacity (2 Specs Available)

1500mAh/DC24V (36Wh)  
3000mAh/DC24V (72Wh)



### Rated Input

DC24V/1.25A



### Rated Output

DC24V/2.5A



### Other functions

UPS  
Charge and discharge  
indicator  
Low battery sound and  
light alarm



### Charging temperature

0 ~ 45°C



### Discharging temperature

-20 ~ 55°C



### Security

Overcharge voltage protection  
Over-discharge voltage protection  
Over-temperature protection  
Charge over-current protection  
Discharge over-current protection  
Short-circuit protection  
Error-proof protection

\*The POS power bank must be charged within the temperature range of 5°C~45°C and discharged within the temperature range of 0°C~45°C.  
If you charge or discharge the POS power bank beyond this temperature range, it will result in the drastic reduction of battery capacity and the shortening of use time.

#### Note:

1. Actual memory will be reduced due to a number of factors and may vary.

2. The actual specs of products launched to the market shall take precedence over the info listed in this catalogue; any change may be made without prior notification.