

# GS R1521 Ruglove Barcode Scanner

## Metal frame structure

With this delicate design, the PCBA is protected from drops and bumps due to the metal protective frame, which ensures reliable operation. Passed the 1 meter 20,000 times rolling test, the performance is reliable.

## Shell material is Hard

The hardness of shell (ABS+PC material) has been greatly improved, is impact-resistant, tensile-resistant, and meets enterprise-grade standards. The imager window (acrylic material) has high strength and strong light transmission.

## QR code scanning engine with ultra-low energy

Global shutter, accurate and fast barcode recognition for mobile scanning scenes. 640×480 resolution, clearer images when scanning barcodes.

## Ruglove Wear

Ergonomically designed, it is still comfortable to wear for a long time. With Ruglove, workers can choose and decide to use left or right hand to work and swap scanning hands on the fly.

## Wide applicability

GS R1521 has unparalleled barcode recognition performance and can recognize almost all 1D and 2D barcodes. USB mode supports keyboard and virtual serial port, adapting to various application interfaces. Supports two modes of classic bluetooth and low energy bluetooth. Support HID, SPP, BLE three transmission protocols.

## Application fields

The scanner can be widely used in manufacturing, warehousing, logistics, retail and express transportation, and has incomparable advantages in improving production efficiency and accuracy.



## ACCESSORIES



Armband  
AB1800



Silicone Glove+Trigger



Lycra Glove+Trigger



Bluetooth Dongle  
GDA201



Battery Charger  
GS GCR201(Dual-slot)



Battery charger  
GS GCR202(8-slot)/203(16-slot)

## PRODUCT SPEC SHEET

### Wearable Barcode Scanner GS R1521

#### PHYSICAL PARAMETER

Scanner Dimensions	66.54mm(L) × 34.73mm(W) × 25.16mm(D)
Scanner Weight	25.8g (scan body)
Battery Capacity	600mAh
Charging	5V---1A
Charging Time	120min
Battery Life	18 hours (scan every 5 seconds)
Notification	LED, Buzzer, Vibration

#### PERFORMANCE CHARACTERISTICS

Optical Resolution	640×480 pixels
Shutter	Global Shutter
Sensor	2D CMOS Image
Skew, Pitch & Roll	Skew tolerance: ±55° from normal Pitch tolerance: ±55° from normal Roll tolerance: 360° from normal
Illumination	White LED
Aiming	Red LED
Supported Symbologies	1D: Code 128(ISBT 128, AIM 128, GS1 128) , EAN-13, EAN-8, UPC-E, UPC-A, ISBN, ISSN, Code11, Interleaved 2 of 5, Code39, Code93, Code32, Codabar, Matrix 2 of 5, Industrial 25, IATA25, MSI Plessey, GS1 DataBar, Plessey, Febraban 2D: QR Code, Micro QR, Data Matrix, PDF417, Micro PDF417, Aztec, Maxicode, Han Xin, Dotcode, Composite
Interface	USB, Bluetooth
Offline Mode	Support storage of 4388 EAN-13 barcodes

#### BLUETOOTH

Bluetooth Protocol	HID Keyboard, SPP, and BLE
Bluetooth Range	Communication distance connected to mobile phone > 164.04ft./50m (without obstructions)
Bluetooth OTA	Bluetooth OTA

#### USB

USB Interface	USB Type-C
USB Protocol	USB HID Keyboard, USB VCP (Virtual Serial Port)
Multilingual Keyboards	USB HID mode supports multilingual keyboards

#### USER ENVIRONMENT

Ambient Light	Max 10000lux (direct sunlight)
Operating Temperature	-10°C~50°C
Storage Temperature	-10°C~50°C
Humidity	5% - 85% non-condensing
Drop Spec.	Multiple 4.9ft./1.5M drops to concrete
Tumble Spec.	Scanner body withstands 20,000 times from 3.3ft./1M with frequency of 10 times per minute.
Electrostatic Discharge (ESD)	±8kv DC discharge, ±15kv air discharge
Certificates	CE, FCC, KC, TELEC, RoHS, ANATEL, NOM, EAC

#### SOFTWARE SUPPORT

Generalscan Keyboard Pro, Generalscan SDK Demo, Generalscan OTA Tools, Generalscan iCode, G-Service

#### DECODE RANGES

13 mil EAN-13	50.0 - 325.0MM
5 mil Code 39	55.0 - 135.0MM
13 mil Code128	50.0 - 330.0MM
15 mil QR	30.0 - 190.0MM
10milData Matrix	40.0 - 130.0MM
6.67 mil PDF417	50.0 - 135.0MM

## GENERALSCAN

#### Generalscan Inc.

200 Buckelew Ave, Jamesburg,  
NJ 08831, USA  
+1 732 895 6821

#### Generalscan Electronics GmbH

Hochstraße 42, 52525  
Heinsberg Germany  
+49 1516 7161256

#### Generalscan LLC

Calle San Luis Potosi 51,  
Roma Norte 06700,  
Ciudad de México  
+52 5552727861

#### GENERALSCAN ELEKTRONIK VE TEKNOLOJİ SAN. VE TİC. LTD. ŞTİ.

FSM Mah. Siir Sk. Relux Plaza No 10,  
Ümraniye 34764,  
İstanbul, Turkey  
+90 542 478 5873